

Woffer for keys **Wall Mount Model** Wall model

Protective Doordog Shutter Door shutter door Release Button Button of

### Instructiontions Open the key storage compartment

- 1. Open the protective doordog
- 2. Enter the opening code (If the equipment is new the code is 0000)
- 3. Press the botopening moment
- 4. Open compartment
- 5. Place what you want to save
- 6.To close
- 7.Shuffle the code
- 8. Close the protective doordog



Compartment of storage of

Key Storage

for storage



Leve

Reset Level

Lever of reposition

Use onsuitable for installation correct

Use level to verify the lock is vertica

Use un nivel para verifica that the candidate is in vertical position



Mark the positioncorrect and level position and the holes for fixing

Mark the position of the screw holes on the surface Mark the position of the screw holes on the surface

# Define a new code

#### The factory code is 0000

- 1. Follow the instructionstions above to open the key compartment
- 2.Change the position of the reset lever from position A to B
- 3. Enter the desired code
- 4. Place the reset lever in the positiontion A again
- 5. Close and test.

#### Installdog

- 1. Open storage compartment (See instructions above)
- 2. Place the equipment in the location to be
- 3.Use the level to check the correct position.
- 4. Mark the position on the surfacetion of the holes for fixing
- 5. Remove the equipment
- 6. Drill the holes for fixingdog
- 7. Install the plugs if necessary
- 8. Put on the equipment
- 9. Tighten the screws
- 10. Close the compartment
- 11. Shuffling the code
- 12. Close protective doordog

## TW08KB

## **Instructions:** Opening the key storage

compartment door

- 1. Open shutter door to reveal the dials and the release button
- 2. Rotate dials to the current combination (if the lock is new, the combination is set at the factory to 0000)
- 3. Press down on the release button to open the door
- 4. Pull the door fully open
- 5. Add or remove keys
- 6. Close compartment door
- 7. Scramble the combination dials to lock the door and conceal your combination
- 8. Close the shutter door

### **Instructions:** When opening the compartment door to

- 1. Open the shutter door to reveal the dials and the release button
- 2. Rotate the dials to the current combination (if the request is new, the combination is established at the factory at 0000)
- 3. Press the release button to open the door
- 4. Hale the door until it opens completely
- 5. Add the keys

key storage

- 6. Close the compartment door
- 7. Mix the combination dials to close the door and hide your combination
- 8. Close the shutter door

#### To set a new combination:

The initial combination is set at the factory to 0000.

- 1. Open the compartment door (see instructions above)
- 2. Push the reset lever from A to B
- 3. Rotate dials to your desired combination
- 4. Push the reset lever, to position A again
- 5. Close the key storage compartment door
- 6. Scramble the combination dials to lock the door and conceal your combination
- 7. Close the shutter door

## To hang a wall mount model

- 1.Open the compartment door (see instructions above)
- 2 Position the lock on the desired surface
- 3. Use level to verify the lock is vertical
- 4. Mark the position of the screw holes on the surface
- 5. Remove lock
- 6 Drill holes
- 7. If necessary, use hammer to place anchors
- 8. Position lock
- 9. Insert and tighten screws
- 10. Close compartment door
- 11. Scramble the combination dials to lock the door and conceal your combination

Certifiedqbe sure to register your code. Gkeep in a safe place.

Be sure to record your combination. Save in a safe location. Be sure to register your combination. Almacene en un lugar seguro.

12. Close the shutter door

### To configure a new combination:

The initial combination is established at the factory at 0000.

- 1. Open the compartment door (see previous instructions)
- 2. Push the reset lever from A to B
- 3. Rotate the dials according to the desired combination
- 4. Push the reset lever from A to B, returning to the original position
- 5. Open the compartment door for key storage
- 6. Mix the combination dials to close the door and hide your combination
- 7. Close the shutter door

#### To hang the wall model

- 1. Open the compartment door (see previous instructions)
- 2. Place the canda on the desired surface
- 3. Use a level to check that the canda is in a vertical
- 4. Mark the position of the screw holes on the surface
- 5. Retire el candado
- 6 Perfore los orificios
- 7. If necessary, use a hammer to place the elders
- 8. Place the candidate in its position
- 9. Insert and tighten the screws
- 10. Close the compartment door
- 11. Mix the combination dials to close the door and hide your combination
- 12. Close the shutter door